



VERTICAL SHAFT IMPACTOR WITH
SUSPENDED IMPELLER

5

BACKGROUND OF THE INVENTION

This invention relates to rock and ore crushers, and more particularly to crushers
of the vertical shaft impactor type which are arrange to direct rock and ore material
onto a rapidly rotating impeller structure that expels the material outwardly at high
10 speed for shattering impact of the expelled rock and ore material within the crusher
into smaller fragments and fines which are discharged from the crusher as desired,
crushed product.

Next to food, clothing, and shelter, rock in useable form is the most important
product of advanced society. It is essential for building homes, roads, buildings,
15 dams, ~~airports~~ airports, railroads, and other uses for human benefits. Rock in gravel
form where deposited is less costly to process than quarry rock, but in either form it
rarely can it be used as found, consequently it must be reduced to required sizes; in
some third world countries rock is manually crushed with hammers where one
person might produce a ton of rock per day of rock in sizes mostly too large for best
20 usage. In modern societies rock is crushed in enormous volumes by machinery and
few workers. Rock crushers are normally used in three or more sequential stages:
First a compression type primaries either jaw or gyratory for large size rock, second
stage usually gyrating cone type for reducing oversize rock from the first stage to

larger useable sizes, and tertiary stage for the smallest but very essential sizes. It is very difficult to produce fine crushed rock with compression type crushers; the stresses are very high and volume is low and the wear rate of wear liners is costly.

Since the mid twentieth century a form of crusher called a "VSI" in the trade, an acronym for Vertical Shaft Impactor, was invented; it uses a high speed impeller mounted on the top end of a vertical shaft. It throws the rock against metal anvils. Many different manufacturers have brought this concept to market, but the extremely high costs of maintenance both in parts and frequent need of labor to change impeller slingers and anvils has been a bane to their success. There is another design of VSI that crushes rock on rock which eliminates anvils and their high costs, but it has less crushing efficiency and higher power demand per ton of net product; it uses essentially the same mechanics as does the anvil design except the rock chamber. ~~Our~~ The design in this patent application is a new concept of the mechanics of rock on rock crushing; it is substantially easier and faster to service and reduces the costs of fine crushing to be very acceptable.

BRIEF SUMMARY OF THE INVENTION

~~A Vertical Shaft Impact crusher having a rectangular frame supported above four upright parallel columns and braced for rigid construction. A rectangular plate means midway to the length of said frame and supporting a hollow spindle suspended by a single antifriction bearing contained within an annular enclosure having sealing means to exclude contaminants and retain lubricants; said enclosure supported by flexible means to absorb harmful vibration and unbalancing forces. An inverted cup shaped vee belt sheave attached to the top end of said hollow spindle and having an equal number of vee grooves above and below the radial centerline of said bearing. At the lower end of said spindle a modified gunlock connection between spindle and an impeller; said impeller having two or more ports to eject propelled rock or ore at high velocities to collide with other rock or ore and cause breakage of same. A static tube within said spindle to conduct rock or ore into said impeller. An enclosed chamber surrounding said impeller and mounted on an elevating frame means that is raised and lowered by power means to provide access to service or exchange impellers. Hooklike means automatically attach to elevating frame when it is raised to working position are unhooked by cams to lower frame. Means to insure even lifting and lowering of elevator frame. A hopper is under said chamber with a telescoping extension. Two opposed power means suspended below swingable bases having stabilizers and roller supports; multiple vee belts transfer power means to said cup shaped sheave attached to said spindle; belts tensioned by power means connected in parallel preset to achieve correct belt tension. Lubricating~~

~~pump powered by a small motor prior to and during startup; power transfers to one of two opposed power means when it reaches full speed. Oil lines to and from bearing to a reservoir. Auxiliary hydraulic power means to raise elevator frame and swing motor bases. A manually swingable boom to change impellers.~~

- 5 In its basic concept this invention provides a suspended impeller rock and ore crusher apparatus arranged to support an impeller member on the bottom end of a hollow, rotating drive spindle, open through its opposite ends, and supported by a bearing assembly in vertically suspended condition by the crusher main frame, for passage of rock and ore material to be crushed from a feed hopper, through the
10 hollow interior of the spindle and to the impeller, whereupon the material is ejected at high speed from the rotating impeller and into shattering impact within an encircling annular rock impact chamber, the chamber preferably being supported on the main frame for vertical movement between an operative, impeller-encircling position and a maintenance position in which the chamber is moved vertically out of
15 impeller-encircling position for facilitated inspection, servicing and replacement by maintenance personnel.

- Another object and advantage of this invention is the provision of a crusher apparatus of the class described in which the impeller-supporting drive spindle support bearing is a single antifriction bearing assembly contained in an enclosure
20 providing a sealing arrangement to exclude contaminants and retain lubricants, and is supported on the main frame to absorb vibration and unbalancing forces from the rotating spindle and impeller supported thereon.

Another object and advantage of this invention is the provision of a crusher apparatus of the class described having a protective, hollow static tube extending through the hollow interior of the rotating spindle member for communicating rock and ore through the hollow interior of the spindle member while preventing
5 damaging contact of the material with the interior surfaces of the rotating spindle member.

A further object of this invention is the provision of a crusher apparatus of the class described having a spindle drive arrangement utilizing a pair of opposed, motor-driven, spindle-engaging belt drives engaging the spindle above and below its
10 bearing mount, the belts being selectively tensioned to assure against binding forces between the rotating spindle and supporting bearing.

A further object and advantage of this invention is the provision of a crusher apparatus of the class described which may include a swingable maintenance boom apparatus on the main frame for supporting and moving impeller members being
15 changed during maintenance operations.

A still further object and advantage of this invention is the provision of a crusher apparatus of the class described which is of simplified construction for economical manufacture and maintenance.

The foregoing and other objects and advantages of this invention will appear
20 from the following detailed description, taken in connection with the accompanying drawings of a preferred embodiment.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

Page 1 FIG 1 ~~shows is a side-vertical side elevational view of the invention with~~
~~viewable parts numbered; both sides are identical a crusher embodying features of this~~
5 invention.

Page 2 FIG 2 is a ~~partially sectioned view showing rotating members, drive~~
~~sheaves, and vee belts, and member 21, an annular chamber, and its elevator frame 7~~
~~in working position, and secured by our latching design.~~ side elevation generally
similar to FIG 1 but with parts being broken away to show internal detail hidden from
10 view in FIG 1.

Page 3 FIG 3 ~~shows member 21 in lowered position to give access to service~~
~~impeller 60; is a side elevation of the annular chamber and impeller structure of FIG 2~~
but with the annular chamber shown in its lowered, maintenance position.

FIG 4 is a fragmentary plan view of our method an arrangement to insure even
15 raising and lowering of elevator frame 7.

FIG 5 ~~depicts one of several different means of customer installations is a~~
fragmentary side elevation of a discharge apparatus for receiving crushed product
from the annular chamber and transporting it for additional processing.

Page 4 FIG 6 is a plan view of the top side having of the crusher with the top
20 ~~hopper removed and sectioned views of the chamber cover 48 to show wedging~~
~~method 103, drive sheaves on motor shafts and vee belts to driven sheave 50, and a~~
~~belt drive 108 to power a lube oil pump. Swingable motor bases 85 moved by~~
~~hydraulics 87 and a swing boom to assist in changing impellers are shown.~~ removed,
parts being broken away to show internal detail otherwise hidden from view.

~~FIG 7 details a wedging system~~ is a fragmentary sectional view of a wedging arrangement.

~~Page 5 FIG 8 shows~~ is a plan view of ~~said the annular~~ chamber partially sectioned and ~~showing~~ a simulated propelling of ~~rock; rock~~.

5 FIG 9 is a vertically sectioned view of the ~~chamber; annular rock chamber~~.

FIG 10 is an enlarged end view of a wedging ~~buttress; buttress~~.

FIG 11 is an enlarged sectioned view of an elastomer seal seated on a steel ~~support; support~~.

FIG 12 is a side elevational view of a wedge.

10 ~~Page 6 FIG 13 is a plan view of a containment and wear protector~~ ~~ring; ring~~.

FIG 14 is ~~a vertical exploded and sectioned an exploded, vertical sectional~~ view through the ring arrangement of FIG 13; 13.

FIG 15 is an exploded- vertical sectional view of a wedging ~~system; arrangement~~.

FIG 16 ~~shows~~ is a vertical sectional view of the parts of FIG 15 in fully assembled
15 condition as would be viewed from the right in FIG 15.

~~Page 7 FIG 17 shows~~ is a foreshortened, sectional side elevational view of the elevator ~~frame; frame~~.

FIG 18 is an exploded end elevational view of ~~how its parts assemble the~~
assembly of FIG 17 as viewed from the right in FIG 17.

20 ~~Page 8 FIG 19 is a vertical sectioned view of the main rotating parts of our~~
~~invention; the crusher of this invention~~.

FIG 20 ~~shows~~ is a vertical sectional view of a lube oil injection nozzle.

~~Page 9 FIG 21 is a vertical sectioned view of an~~ ~~impeller; impeller~~.

FIG 22 shows the back view, cross-section view, and a sectioned view of a wear tip clamped in working ~~position;~~position.

FIG 23 ~~shows the method of~~ is a bottom plan view of an arrangement for retaining the distributor plate.

5 ~~Page 10~~ FIG 24 is a plan view of the top face of an ~~impeller~~impeller, parts being broken away and sectioned to show its associated ~~parts;~~ parts otherwise hidden from view.

FIG 25 is a cross-sectioned elevational view of a tip holding member.

10 ~~Page 11~~ FIG 26 is a plan and corresponding edge view of a combination wear and camming ~~disk;~~ disk.

Fig 27 ~~details~~ is a fragmentary plan view of a cam slot; slot.

FIG 28 is a side elevational view of a sliding ~~means-bar member~~ driven by said cam slot.

15 ~~Page 12~~ FIG 29 ~~shows a~~ is a fragmentary vertical elevational view of ~~a means-an~~ arrangement to turn a large ring like nut by gear ~~means;~~ apparatus.

FIG 30 is a plan view of a driving gear within a housing joined to a ~~yoke;~~ yoke.

FIG 31 ~~details~~ is a fragmentary plan view showing the connection of the yoke to a spindle.

~~Page 13~~ FIG 32 is a plan view of a swingable motor ~~base;~~ base.

20 FIG 33 is a fragmentary vertical view of ~~said the~~ -motor base; base of FIG 32.

FIG 34 ~~shows~~ is a fragmentary vertical elevation of the the pivot ~~means arrangement~~ and stabilizers means for ~~said the~~ motor base; base of FIGS 32 and 33.

FIG 35 ~~shows a~~ is a fragmentary vertical elevational view of the roller means
apparatus supporting said motor base opposite said pivot means.

~~Page 14~~ FIG 36 is a ~~vertically sectioned~~ fragmentary, vertical sectional view
showing a ~~means of an~~ arrangement for rock crushing against impact anvils instead of
5 rock on rock ~~crushing; crushing.~~

FIG 37 is a fragmented plan view of one form of several possible shapes of impact
anvils and a ~~means of an~~ arrangement for their containment, containment.

FIG 38 is a ~~back~~ rear elevational view of an impact ~~anvil, and anvil.~~

FIG 39 ~~shows a means of~~ is a fragmentary vertical sectional view of an
10 arrangement for holding anvils against its containing annular wall.

~~SPECIFICATION OF APPLICATION~~

5 ~~NAME OF INVENTION: VSI CRUSHER WITH SINGLE BEARING SUSPENDED~~
~~IMPELLER~~

~~Inventors; Louis Wein Johnson, citizen of the USA, residence 345 Palomino Dr., Eugene, OR 97401. Bruce Gordon Johnson, citizen of USA, residence 26710 Alpine Cutoff Rd., Monroe, OR 97456~~

DETAILED DESCRIPTION OF THE INVENTION

FIG 1:- In FIG 1, #1 represents the full side view of a complete machine; its
 15 opposite side is virtually identical. #2 is one of two longitudinal main frame beams
 each composed by having two unequal leg angle irons joined by welds to form a
 stepped 90°Z; ~~cross~~90°Z. Cross beams 3 are at each end of beams 2 and space said
 beams 2 apart a designed ~~distance~~; not distance. Not shown are X bracing of vertical
 columns 4 90° to beams 2; ~~horizontal~~ 2. Horizontal beams 5 space columns 4 to
 20 parallelism and with angle braces 6 provide a very stiff ~~structure~~; 7 is structure.
#7 illustrates one of two parallel beams joined at their ends by channel beams 130
 that forms a frame ~~we call an “Elevator”~~; see Page 7 herein referred to as an elevator.
 When the elevator is in working position four hooks 10 hold it from ~~dropping~~;

dropping. Two sets of roller chains 14 and 15 connect to equalizer means 17 which connects to the cylinder rod of hydraulic cylinder 18 which is anchored at ~~19; both~~ 19. Both #14 chains engage the teeth of inner sprocket 12 less than 90° and connect to said elevator at ~~145; 145,~~ and both chains 15 wrap the outer sprockets of 12 180° and
5 connect to rod ~~16; two~~ 16.

Two second sections of chains 15 connect to the other end of 16 and roll over sprockets 13 and connect to adjustment means in bracket ~~33; the~~ 33. The length of rod 16 is the distance between sprockets 12 and 13 minus the stroke of cylinder 18 minus enough chain links to avoid contacting either sprocket; double sprockets 12
10 and single sprockets ~~13, 13.~~ 13. ~~(means 16, 17, 18 and 19 are better explained on Page 3 FIGs 3 and 4); means 20~~

#20 are brackets that support sprockets 12 and ~~13; 13,~~ and #21 is an annular chamber open at top and partially open at bottom for crushed product to exit into and through conical chamber 22 and telescoping extension 23. #24 are two risers to support
15 hopper 25 above a belt drive system; both 24s risers 24 have passage ways to bypass material to be crushed and passage ways for air ~~recirculation; lever~~ recirculation. Lever 26 controls an air damper vane and is lockable through 90°; #27 is a hopper extension usually supplied by the customer.

#28 are drive motors opposed 180°; #29 is a motor pump unit providing hydraulic
20 power as ~~needed; needed,~~ and 30 is its oil reservoir. 31 is lube oil motor pump direct connected to pump ~~83; that~~ 83 which prelubricates an antifriction bearing before motors 28 are ~~started; an~~ started. An overrunning clutch mounted on pump motor's top shaft extension allows the pump motor to run before motors 28 ~~start; because~~

start. Because drive shaft assembly 34 is driven by one motor after that motor is at full speed and powers lube pump through the lube motor's ~~shaft;~~ shaft, the overrunning clutch locks-up, and power to the lube motor is shut ~~off;~~ off. 32 is its oil reservoir, and oil returns to it in a closed circuit; the oil is filtered. A special grade of oil is required because of the high bearing speed imposed. A swinging boom 35 having a cradle 36 is used to exchange an impeller 60, ~~Page 2 FIG 2;~~ (FIG 2), and a hydraulic jack 38 lifts and lowers said boom vertically; bracket 39 supports said jack. 70 are light weight covers spanning the width of the main frame shielding all moving parts from inclement weather.

10

~~Page 2 FIG 2~~ FIG 2 is a fragmented view showing the main rotating parts sectioned through their center of ~~rotation;~~ rotation. Sheaves 80 and 81 on their respective motor ~~shafts, 28S;~~ shafts 28S are vee belted to driven sheave ~~50;~~ belt 50. Belt 83 is a multistrand belt centered over ball bearing ~~165;~~ 165, and twin belts 84 each ~~having have~~ one half as many strands as 83 straddle ~~83;~~ this 83. This design eliminates any bending or tilting forces on bearing 165 caused by belt tension or motor torque pulling. Detailed construction of this design is ~~on Page 8~~ shown in FIG 19.

20 Sheave 50 is attached to hollow spindle 51 with multiple cap ~~screws;~~ screws, and spindle 51 is journaled in bearing 165 which in turn is contained in ~~housing, 167;~~ base housing 167. Base plate 56 supports 167 through a flexible ring ~~173;~~ 173, and an impeller or rotor 60 is attached to said spindle by a quick attach and release gun lock

~~design;~~design in which a large nut 58 forces and retains a secure coupling of the gun
~~lock; the lock.~~ This nut has gear teeth around its circumference to enable one person
to tighten the nut to required torque ~~with a device shown on Page 12.~~

___Rock or ore to be crushed is conveyed to hopper 27 where it falls onto choke ring
5 74 and down stationary tube 73 into impeller 60 which has spinning speeds sufficient
to break both ejected rock and other rocks that are in suspension previously ejected or
that have fallen through bypass chutes 47. Chamber 21 contains a bed of static rock or
ore sloping from wear ring 41 upward and outward at whatever angle of repose is
taken. Multiple vanes 115 form compartments and support a containment ring
10 detailed on ~~Page 6;~~ 6 of the drawings.

___An extremely violent activity occurs within the rock chamber as the energy of
several hundred horsepower is converted to accelerating a stream of rock or ore to
over 250 feet per ~~second;~~second, with broken rock and dust ~~are~~ swirling in a tornado
of abrasive atmosphere. To protect expensive parts we provide low cost protective
15 means: ~~the~~ The top surface of impeller 60 is protected by disc 57, and spindle 51 and
gear nut 58 are protected by static annular members 77 and ~~78;~~78. The member 78
telescopes into 77 when access to nut 58 is necessary to change ~~impellers;~~impellers,
and the perimeter edges of the impeller are protected by welds of abrasion resistant
metal.

20 ___#64 serves as both an impact and distributor plate and can be of several different
shapes of its top surface. 117 is a rectangle of angle iron extending upward above
chamber 21 and is bolted to the top flange of ~~21;~~ a 21. A commercial channel rubber
121 snaps over the upstanding edges of 117 and seals against the underside of plate

56. #45 are brackets to which hooks 10 are pinned; 44 are latching pins for ~~hooks;~~
hooks, and 43 are cams keyed to cross shafts and bear against each ~~hook; tee hook.~~
Tee handles 42 provide manual leverage to turn all cams from one side of the
~~machine; when machine.~~ When elevator 7 is to be lowered a slight upward lift is
5 made to release its weight on the ~~hooks; elastomer hooks.~~ Elastomer 121 yields
enough to permit releasing said ~~hooks; hooks, and~~ levers 42 are turned to force cams
to push hooks clear of pins 44; ~~this 44, which~~ allows the elevator to be lowered by
gravity. Hooks are shaped to automatically latch over pins 44 when elevator is raised
to working position. 40 are replaceable wear liners to protect conical hopper 22.

10 ~~Page 3~~ FIG 3 shows the elevator in down position with chamber 21 resting on
beams 5, and 23 telescoped into hopper ~~22; 22.~~ #18 is one of two identically mounted
hydraulic pull cylinders connected in parallel by hydraulic hoses 54 and then to a
control valve not ~~shown; shown.~~ 19 is its anchor bracket and 18R its extended
cylinder rod; swing boom 35 is positioned for its cradle 36 to receive impeller ~~60; a~~
15 60. A jack 38 either hydraulic or mechanical raises or lowers the boom as its pivot
shaft slides in bearing brackets ~~37; geared 37, and~~ nut 58 is unscrewed just enough to
free the gun ~~lock; jack lock.~~ Jack 38 raises the impeller just enough to allow manual
turning of spindle 51 to where the gun lock will allow separation of the impeller from
the ~~spindle; the spindle.~~ Then the boom with impeller is lowered and swung outward
20 to a position that will allow exchanging for another impeller.

FIG 4 is a plan view of the means to insure even and controlled lifting and
lowering of the ~~elevator; timing elevator.~~ Timing shaft 90 has universal joints 91
coupled to short shafts 92 which are journaled in self aligning bearings 95 contained

in two piece spherical housings 93 and 94 at inside position and brackets 20 and the same caps 94 at the ~~outside; dual~~ outside. Dual sprockets 12 are keyed to shafts 92 and are staggered one half their tooth pitch as a preferred option, but it is not necessary to ~~stagger; stagger~~. 17 is a means to equalize chain loading. 17L and 17S
5 connect 17 to each chain and their length difference is one half the chain pitch. Chains 14 roll over the inner sprockets then descend directly to brackets ~~145; chains~~ 145. Chains 15 make a 180° turn around the outer sprockets and connect to rods ~~16;~~ 16, and second sections of chains 15 join to rods 16 and to adjustable anchors ~~146;~~ rods-146. Rods 16 are used to make chain lengths as short as possible because chains
10 tend to stretch and hang in a sagging curve that affects their lengths adversely, and would making an even lift of the elevator very ~~difficult; the~~ difficult. The mechanics of both sides are identical.

FIG 5 shows the need for member 23 to telescope into 22, because conveyer 101 ~~an~~ and hopper 100 are immovable and to permit the elevator assembly to be ~~lowered~~
15 ~~we~~ lowered. We choose this way to accommodate elevator lowering. Vertical shaft crushers generate considerable dust which must be ~~contained; contained, and~~ this is best done by air vacuum drawing off dust from a conveyor belt hopper a short distance beyond where 23 joins with the hopper 100 which is enclosed except where the conveyor 101 carries crushed products beyond hopper ~~100; the~~ 100. The dust
20 laden air is cleaned in bag houses.

~~Page 4~~ FIG 6 is a plan view of a complete machine less motors, top hoppers 25 ~~and 27 and~~ 27 and covers 70. Main power motors 28 are suspended from steel plates 85, which pivot at ~~86; 86~~ and are stabilized and supported level by two supporting

roller assemblies opposite to the pivot, and two screw adjusted pads near the edges of plate 85 and slightly offset to pivot ~~86~~86, (~~as detailed on page 13~~); ~~13 of the drawings~~). ~~push-pull~~ Push-pull hydraulic cylinders 87 anchored at 88 are connected in parallel with hydraulic hoses and to a control valve which is supplied by pressurized oil from pump means 29, shown in FIG 1; ~~this 1~~. This system tensions belts 83 and 84 in the push mode to proper tension by an adjustable relief valve and bases can be pulled to release tension at down time to increase belt life and give ample slack to facilitate easy belt replacement.

24 are two supports to raise hopper 25 above sheave 50 to provide top and side clearances for changing belts over sheave ~~50~~; ~~when 50~~. When vee belts are changed it is necessary to remove feed tube ~~73~~; 73. #47 are bypass chutes to increase crushing efficiency and capacity and to confine overflow within the ~~machine~~; machine. 46 are damper valves that can be used to control the circulating air that passes through the impeller along with material to be crushed by ~~impact~~; air-impact. Air volume varies inversely with volume of material passing through ring 74 FIG 2; 2, and recirculating the air reduces its outflow through hopper ~~23~~; the 23. The tilt of 46 is controlled by exterior lever 26.

#102 is an expandable sectioned containment ring that prevents turbulent crushed rock from impinging against the mild steel cover plates ~~48~~; ~~sections 48~~. Sections of 102 are expanded by wedges 103 detailed in FIG 7; 7. 107 is a pulley mounted on a shaft journaled in a bearing housing (~~110 FIG 33 page 13~~) 110, FIG 33, and coupled to shaft 34 by a universal joint FIG 1; a 1. A vee belt 108 driven by pulley 109 mounted on motor shaft 28S drives pulley 107; said bearing housing is slidable for

belt ~~adjustment; when adjustment.~~ When the main motors reach full speed one motor drives the lube oil pump 83 through motor shaft of ~~31; 31,~~ and power to 31 is shut off, ~~this off.~~ This system prevents stoppage of lube oil to bearing 165 by electric power failure. Coasting time of main motors and spindle after power is cut off is several
5 minutes, and this design insures the ball bearing would not be destroyed by lack of lubricant.

FIG 7 shows one of several elongated wedges 103 forced between buttress members 106 by bolts 104 to expand segments of 102 to tightly fit the annular wall of chamber ~~21; plates 21.~~ Plates 105 partially cover the gaps between sectors of 102 and
10 bolt nuts are tack welded to 105 because the nuts are not ~~very very~~ very accessible for a wrench. 114 is one of four lifting attachments.

~~Page 5~~ FIG 8 is a plan view of the rock chamber ~~21; 21.~~ #115 are multiple vanes set approximately tangent to the rim of the impeller ~~60; 51 is a section through spindle 51; 60.~~ #58 is the geared nut, and 73 is the stationery down tube through
15 which crushable material ~~drops; a drops.~~ A simulation is shown of rock falling through 73 and flowing outward against a static a layer of rock retained by arcuated walls 204; the flowing rock rolls toward and over carbide tips where it leaves the impeller at very fast ~~speeds; as speeds.~~ As the bed of rock rolls toward the tip it is subjected to several Gs of pressure which causes considerable rock on rock crushing
20 and abrasion before the rock leaves the impeller.

Rectangular frame 117 supports the inner edges of cover plates 48 with a wedging ~~system, system.~~ FIG 10 shows buttress blocks 118 having channels 119 to retain wedges 120, FIG 12, which are set to the angle of the wedges and are welded to the

upright legs of 117 ~~frame; the frame.~~ The wedges press plates 48 firmly against the outer projecting legs of the angle iron members of 117 and can be set and removed ~~quickly; the quickly.~~ The perimeters of plates 48 are bolted to the top annular angle iron flange of chamber ~~21; 21.~~ Channel rubber 121 detailed in FIG 11 is a commercial product and is used to seal the chamber assembly against base plate 56 to prevent the escape of crusher dust. FIG 9 is a vertical cross sectioned view through the chamber assembly showing containment ring 102 with wear resistant plate 116 resting on the top edges of vanes 115; it also shows wedges 120 in place.

~~Page 6~~ FIG 13 is a plan view of containment ring 102 and one of its wear plates ~~116; 116, and~~ 123 is an inner segmented ring welded to arcuated sectors ~~102; 102.~~ FIG 14 is an exploded vertical sectioned view of ~~102; sectors 102, and~~ #122 is a wear ring that fits over the depending portion of 123 and becomes secured in position when 102 is expanded by wedges as in FIG 16; 16. #116 have at least one bolt to hold each to 102 until they rest on vanes 115.

FIG 15 is a vertical exploded view of the wedging assembly, and FIG 16 shows a side on vertical view of a finished assembly. The purpose of this expandable member is protect the top cover from abrasion of flying rock, and its wedge design makes a quick way to install and replace, and a tight fit against the chamber wall holds it securely in place.

~~Page 7~~ FIG 17 is a detailed vertical sectioned view of one side of the elevator frame; the other side is a mirror image. Plate 9 is configured to partially overlap the lower flange of I beam 7 to provide parallelism to the web of the beam, maximum space for rollers 8, and to provide for a strong fillet ~~weld; its weld.~~ Its top extension

provides an anchor attachment 145 for a roller chain connecting link and a partial fillet weld space as ~~below;~~ below. Plate 33 extends higher than 9 and is slotted to allow adjusting means 146 in horizontal beam 147 to extend the same distance beyond 145 as the space between double chain sprockets ~~12;~~ 12. A threaded member
5 146 has flats milled to the width of a chain link and a hole drilled to the size of a chain pin; a jam nut above beam 147 and a full thickness nut below provide for adjusting chains for parallel lifting and full seating of seals 121 against base plate 56.

#150 are upstanding members drilled at 151 to receive pins 152 for hooks 10 to ~~latch;~~ and the angles α are to facilitate engagement of hooks when the elevator is
10 raised to working position. 133 are angle irons with low friction slideway material 134 bonded to their projecting legs. 142 is a threaded hole to receive cap screw 141
FIG 18.

FIG 18 is an exploded view at right angle to beams 7; ~~# 130-7;~~ and #130 are channel iron crossbeams weld to the ends of I beams 7 to form a rectangular ~~frame;~~
15 ~~four frame.~~ Four rollers 8 are journalled on cam axles 136 which pivot in plates ~~9and9~~ and 33 at axles outer ends and within bushings 137 which seat in the I beam's web and allow cams of 136 to be assembled through enlarged holes in beam's ~~web;~~ web. #137 follow cams and journal cams concentric to bearing holes in members 9 and ~~33;~~ cam 33. Cam axles are rotated by turning discs 138 with a wrench on the
20 nuts welded to each ~~138;~~ the 138. The nuts are locked to each axle with anaerobic thread locking fluid which bonds strong enough to turn cams but can be broken free to separate parts if needed to repair.

Cam axles are rotated to bring rollers to lightly touch uprights ~~4;4,~~ and third class levers 139 have fulcrum on bars 140 welded to their extreme ends and are clamped to discs 138 by cap screws ~~141; the 141.~~ The cam axles are locked from rotating thereby retaining their adjusted positions. Angles 133 having the low friction slide material bonded to one leg can be adjusted horizontally by elongated slots 153 sliding over and retained by bolts ~~154; not 154.~~ Not shown are polished steel guides welded to insides of the flanges of columns 4 for ~~134~~ material 134 to slide ~~against; this against.~~ This construction forms a guided elevator frame. This design provides stability to the entire elevator assembly and resists the impacting forces of impinging rock attempting to rotate the rock chamber.

~~Page 8~~ FIG 19 is a vertical sectioned view of the main rotating mechanism. Driven sheave 50 is of two piece fabricated steel construction to attain required strength, low cost of manufacture, and minimum replacement ~~costs; annular costs.~~ Annular rim 50 is rolled steel plate welded at closure of the roll, stress relieved, and fully ~~machined; an~~ machined. An internal thread is cut at 162 to a shoulder; and plate member 163 is fully machined and threaded into 50 using an anaerobic thread locking fluid to firmly seat against said ~~shoulder; the shoulder.~~ The hand of thread is in the direction that the driving forces will tend to tighten the thread against said ~~shoulder; the shoulder.~~

The cup shaped construction of sheave 50 is to achieve balanced belt pull applied to bearing ~~165; multiple 165.~~ Multiple cap screws 164 join sheave 50 to hollow spindle 51 and is centered to spindle 51 at diameters ~~52; labyrinth 52.~~ Labyrinth seal 192 is retained to sheave 50 by a slight positive angled taper having an interference fit

and is assembled by either expanding the open end of sheave 50 with heat or contracting seal 192 by cooling. #51 is thick walled tube or pipe having an internal diameter large enough to have adequate running clearances around a depending tube 73 and an outer diameter large enough to provide machining to accept a stock size anti-friction bearing such as 165, ~~plus 165,~~ along with a first shoulder diameter for ring 186 positioned between the bearing and first shoulder; plus a second shoulder for positioning seal 191.

Ring 186 has a band 187 secured to it and with 188 which is secured to member 169 ring form a deep labyrinth seal; ~~in seal.~~ In addition to first and second shoulders diameters are added larger diameters 197 and thread diameter 198. The bore of 51 is slightly tapered outward above and below the midline of bearing 165 to accommodate any wobbling of the ~~spindle; wobbling spindle.~~ Wobbling can be caused by unbalanced forces within impeller 60.

Conical ring 183 has a flange for cap screw attachment to housing 167 and serves as a lube oil ~~retainer; retainer,~~ and annular nut 166 clamps bearing 165 between it and 186 and enables said bearing to carry the weight of all depending members. Only a ball bearing will cope with the very high speeds required plus thrust loading in both directions, and moment loading caused by an out of balance rotor. In well balanced operations the thrust loading of this bearing is very light, and it has a long life ~~potential; however, potential.~~ However, the high ball speeds require a special oil that must be applied by spray injection above and below the rolling ~~balls; the balls.~~ This oil is conducted by hydraulic hoses, not shown, from pump 83 to inlets 178 and ~~179; drilled-179.~~ Drilled passage ways conduct oil from 178 to nozzle 185 (detailed in

FIG 20) that is retained by cap screws against a flat surface milled in housing ~~167~~ 167.

An elastomer seal ring 195 prevents oil leakage between nozzle and ~~housing; lube~~ housing. The oil sprays ~~upward; upward,~~ and an opposed oil passage from 179
5 conducts oil into bearing clamping ring 168 which is drilled to conduct oil to spray
onto balls from above. The flanged conical member 183 diverts oil that may be
ejected above the bearing to fall back and through the bearing and to prevent any oil
to escape between sheave 50 and housing 167. Housing 167 is either formed from a
rolled and welded band or flame cut from a thick ~~plate; it plate~~. The housing is
10 machined to retain bearing 165, threaded to receive member 169, which is
permanently bonded to 167 and has a conical diverging bore for oil drains 182. #171
is an annular plate sufficiently thick to shoulder into ~~167, have 167~~. It has a boss to
retain labyrinth seal 193 have oil passages 178 and 179, and receive member 172
recessed into it.

15 The ID (inside diameter) of member 171 is configured to retain seal 189 ~~having~~
~~and has~~ small cap screws to retain said seal and with space above for clearance for the
heads of said screws without interference from 169. #172 is an annular flat ring
having an OD (outside diameter) to fit into 171 and an ID projecting inward past a
flexible member 173 far enough for cap screw attachment to 179 but slightly larger
20 than seal ~~189; member 189~~. Member 174 is a ring fully welded to annular plate 175;
its ID is machined to fit boss 176 of base plate member ~~56; 56,~~ and its OD is as flame
cut. The inside surface of 174 is machined conical and the top surface of 175 is
prepared for bonding as is the under side of ~~172; these 172~~. These three members are

bonded to a low durometer elastomer 173 that is oil and atmosphere ~~resistant; some~~
resistant. Some additional molding parts are used in the molding process to contain
the elastomer but are treated to prevent being bonded and are removed after bonding
and curing are completed. This mechanism absorbs all but the most severe wobbling
5 and protects companion parts from ~~damage.197-damage.~~

197 is a cylindrical area with two or more pair of recessed holes 194; each pair of
recessed holes are 180° ~~apart; their purpose is explained on page 12 following.~~ apart.
180 are two or more evenly spaced conical sectors with cylindrical sectors between
that are slightly longer in arc than the conical sectors and are the male elements of our
10 gunlock connection. 181 are partially threaded studs with one or more tangential flats
and are inserted into threaded holes at the trailing end of said conical sectors 180 and
with a tangential flat parallel to those ~~ends; trailing end means relative to the rotation~~
~~of spindle 51.~~ ends. Thread 193 and nut 58 retain impeller 60. #79 is a conical
seating means to center telescoping member 78 to static member 77.

15 ~~Page 9~~ FIG 21 is a vertical sectioned view of an impeller also called a ~~rotor; rotor.~~
200 and 202 are crossrolled steel plates for stronger uniform tensile strength across
their annular shape to form discs having adequate strength to withstand the very high
stresses of centrifugal forces imposed upon ~~them; top them.~~ Top disc 200 is thick
enough for our gunlock design having inward projecting conical sectors 201 that
20 cooperate with the sectors ~~180 FIG 19; the~~ 180, FIG 19. The cylindrical arc length
between each sector 201 is slightly longer than the arc lengths of 180 so as to allow
engagement of the gunlock ~~members; studs~~ members. Studs 181 prevent the gun lock
from disengagement in the trailing direction by engaging ~~201; the~~ 201. The gunlock

sectors are tapered so that a tight and firm connection can be achieved when nut 58 is fully ~~tighten, tightened, and~~ yet release freely when nut is turned ~~open; to open.~~ To prevent the rotor from unlocking in the opposed ~~rotation-rotation,~~ radial slots 217 are machined into disc ~~200~~200, and their function will be explained later.

5 Our gunlock design is much faster and easier to change impellers than other VSI crushers that use a solid shaft with a top end long taper and a matching taper in a hub attached to the single disk of their impeller which is retained by a thick nut that must be fully removed plus the risk of a stuck taper. Discs 200 and 202 are spaced apart by arcuated members 204 and rectangular members 203 all of which are firmly joined by
10 welds; two or more of sets of 203 and 204 are used usually three or five. The production capacity of a crusher of this type is dependent on the number of said sets, their vertical length, and available horsepower.

The openings between members 203 are called "ports." The abrasion rate within an impeller is huge and must be accomodated with easily installed wear resistant
15 members; the most rapid wear is at the tip 206. Many different concepts of rotors and their impelling means have been tried since VSI crushers first appeared in the ~~1950s;~~ the 1950's. The average impeller "shoe" ~~as their called~~ only lasts a few hours as do the static breaker bars that received the impact of propelled rock. The shoes develop valleys and the anvils wear to a cup shape; crushing efficiency diminishes and these
20 two parts rarely use more than 10% of their weight before being replaced.

Our new design is detailed in ~~FIG 22;~~ a FIG 22. A carbide insert is retained in a machined slot in a square steel member ~~207;~~ 207, two faces of which are drilled and ~~threaded; four threaded.~~ Four cap screws are used to hold 207 in a welding and

machining ~~fixture; two fixture.~~ Two faces of 207 adjacent to area to be slotted are hardfaced with weld metal while being held in said fixture to restrain 207 from being warped by the ~~welding; the welding.~~ The welds stop just short of area to be slotted because the hardface weld metal cannot be ~~machined; the machined.~~ The carbide
5 insert is secured in the slot with a high strength anaerobic means.

Steel member 207 is retained by cap screws 208 through holes 210 in member 203 having a machined seating means ~~205 Fig 25 page 10; the 205, (FIG 25).~~ The rock spill over the tip causes extreme wear conditions as it ~~exits; a exits.~~ Accordingly, a wear member 209 protects ~~203; it 203.~~ This member is also ~~carbide; it carbide, and~~ is simultaneously retained with 207 by converging angle θ and its inner vee ~~shape; shape.~~ To achieve maximum tip life tip holder 207 can be turned end for end to use its other set of threaded holes and also be moved vertically to switch positions with its companion because there are two equal length tips in each recess ~~205; each 205.~~ Each tip can be used in four different ~~positions; positions,~~
10 although the lower tip gets the most wear.

Wear plate member 213 is subject to sliding wear and is best made from high chrome chilled iron, but other metals can be used but will wear ~~faster; upper faster.~~ Upper plate 215 usually lasts a long time and can be flame cut from abrasion resistant steel plate. Member 211 is designed to be positioned radially inward or outward and
20 is clamped in set position by bolts ~~212; its 212.~~ The purpose of this member is to control the depth of rock bed as it lays against members 204 and tip 206 and also to prevent spill over at the trailing edges of 204. Distributor member 64 is cast of abrasion resistant metal and is annular in shape as shown in FIG 23 a bottom ~~view;~~

~~inward view.~~ Inward projecting sectored means 63 are spaced apart to allow outward projecting means of mild steel plate 66 to be assembled into 64 and rotated over 63 to enable cover plate 65 retained with cap screws 67, and cap screws 68 threaded into 66 clamp member 64 in operating ~~position;~~ annular position. Annular member 64 can be
5 installed through the gunlock opening or through a port in some rotors.

~~Page 10~~ FIG 24 is a partially sectioned plan view of an impeller top protector wear disc 57 made of wear resistant steel plate machinable with carbide tooling; it has three or more camming slots 216 ~~better illustrated on page 11,~~ shown in FIGs 26 and ~~27; when 27.~~ When an impeller is installed to a spindle member, 57 is rotated with a
10 pin wrench 221 to retract slide bars 218 to maximum outward ~~positions;~~ gear positions. Gear nut 58 ~~has been~~ is turned to a light contact with 57; ~~when 57.~~ When an impeller is positioned against stops ~~181;~~ 181, #57 is rotated in the direction that cam slots engaged by pins 219 push slide bars ~~inward;~~ this inward. This action captures conical sectors 201 between stops 181 and slide bars ~~218;~~ the 218. The
15 thread of geared nut 58 is of the hand will tighten in the direction that tends to turn 57 to push 218 inward relative to the rotation of the spindle. The functions of other members numbered have previously been explained.

~~Page 11~~ FIGs 26 and 27 show radii R-1 and ~~R-2;~~ R-2. FIG 26 shows slide bar 218 in R-2 and R-1 ~~position;~~ position. FIG 28 details slide bar 218 and pin 219 which
20 projects above 218 the thickness of member 57 or slightly less.

~~Page 12~~ FIGS 29,30, 31 show the construction and use of the means of turning gear nut ~~58;~~ 58. #229 is a 180° yoke slightly larger in inside radius than the radius of cylindrical portion 197 of spindle ~~51;~~ section 51. Section 197 has recessed holes 194

that are engaged by screws 230 which have a portion of their threads ~~removed; this~~
~~removed.~~ This locks the spindle relative to small gear ~~225; 225, and~~ screw 232 is
positioned against the spindle to restrain the yoke from rising as gear 225 is ~~turned; a~~
~~turned, as by a~~ wrench having a handle length long enough to apply adequate torque
5 is set on the head of screw ~~226; 226.~~ #226 is bonded to gear 225 with a very high
shear strength anaerobic thread ~~locker; locker.~~

227 is a flat ~~washer; washer, and~~ the outside diameter of teeth of gear 225 is
slightly less than the inside diameters of housing 228 so that the reactive force of
turning gear 58 is absorbed by the housing rather than by screw ~~226; the 226.~~ The
10 edges of the teeth of 225 are rounded to prevent cutting the bore of 228. Holes 194
must be exactly 180° apart to insure proper gear ~~meshing; meshing.~~ The housing 228
is welded to yoke 229. Prior to this design we used two long spanner wrenches that
required two workmen and the wrenches were difficult and awkward to use.

~~Page 13~~ FIG 32 is a plan view of a motor base as used in our ~~VSIC; VSIC.~~ 85 is a
15 flat plate reinforced by flat bars set edgewise under its longitudinal ~~edges; edges, and~~
85 pivots on member 86 and is stabilized against tipping forces that motor torque
applies by means 96 which is detailed in FIG 34; ~~the 34.~~ The opposed end of 85 is
arcuated with 86 being the center of the ~~arc; roller arc.~~ Roller means 62 support 85 in
a level position and minimize frictional resistance to push-pull swinging of 85 by
20 power means 87.

FIG 33 is a vertical view of plate 85 including a section of a motor 28 and drive
sheave 80. ~~#s107, 107,~~ 108, and 109 are an auxiliary drive to lubricating oil pump 83
as previously described. 110 is a bearing housing assembly containing two spaced

apart antifriction bearings a shaft journaled in said bearing and driven by sheaves 109 and 107 and belt ~~108; said 108.~~ The shaft projects below 85 and is coupled to an overrunning clutch, universal joints, and a slip shaft as shown in FIG 1 with #34. 89 are depending angle iron members welded to 85 to provided attaching foot mounted
5 ~~motors; motors,~~ their distance from center is being determined by the frame and size of motors ~~used; means used.~~ Means 82 are flat steel bars attached to brackets welded to 85 and a lifting hole that all large motors have; their purpose is to help support the weight of the motor.

FIG 34 shows one of two 98 upright members welded to base plates and bolted to
10 beam #2; ~~each have 2,~~ each having an internal thread into which cap screw 96 is ~~inserted; the inserted.~~ The top faces of 96 are polished to remove any ~~stampings; at~~ stampings. At assembly each are adjusted to light contact against 85, and then jam nuts 97 are ~~tighen; alset~~ tightened. Also shown in FIG 34 is a partially obstructed view of pivot ~~86; 86-86~~ which is an upright tubular member with an insert at its top
15 and welded to it; ~~said it.~~ This insert is machined to fit the inside diameter of 86 and the diameter of pivot hole in 85 and threaded to receive castle nut 70 which is adjusted to barely allow free pivoting of 85 and is then locked with a cotter pin 71.

FIG 35 shows one of two roller assemblies 62 journaled in support frame 61 and in contact with 85 to support 85 in a level ~~position; position.~~ 63 is a bracket set to
20 slight clearance above 85 to prevent a complete assembly of all components of bases 85, motor, and drive from bouncing on the rollers when the machine is being transported.

Page 14 FIG 36 is a vertical sectioned view of an insertable method of arrangement for converting our invention from crushing rock on rock to crushing against metal anvils. #241 is an annular steel wall of adequate thickness to support breaker anvils set on a conical member 243; means 243. Means 244 and cap screws 245-245, FIG 39, hold each anvil against said wall; a wall. A band 242 with slight clearance 246 encircles 241; 241. The assembly sets on the elevator frame; frame, and essentially the same impeller is used but might have larger vertical ports; anvils ports. The anvils are about twice as long vertically as port depth of the impeller; the impeller. The elevator is adapted to move down and up slowly and pause at each end of travel; this travel. This evens the wear on the anvils and will greatly prolong their useful life, maintain efficient crushing, and minimizing throwaway metal by preventing cupping wear as occurs in the immovable anvils of other vertical shaft impact crushers. To avoid dust escaping a close fitting seal encircles 247 built into hopper 255; 255, and a vacuum air pump draws away dust escaping at gap 246.

FIG 37 is a plan view of one of several different designs possible for anvils; FIG 38 shows the back side of an anvil showing recesses to save weight and casting costs. FIG 39 details one method of retaining anvils in working position; position. 244 is a third class lever fulcruming at its lower end against wall 241 and its top end bearing within a hole cast in a central web of anvil 240; 240, and the cap screw 245 pulls 244 outward.

From the foregoing carefully detailed identification and description of the various structures and structural elements and parts of a preferred embodiment of the rock and ore crusher apparatus of this invention, it will be apparent to those skilled in the

art that the invention provides a suspended-impeller crusher apparatus in which a rock
ejecting impeller member is secured onto the bottom end of a vertically-suspended,
rotating, hollow drive shaft, identified herein as a hollow drive spindle. This
impeller-supporting spindle member is open through its opposite terminal ends, its
5 hollow interior communicating through its open top end with a feed hopper and
through its bottom open end with the interior of the impeller member, for passage of
rock and ore material to be crushed from the hopper through the hollow, rotating
spindle and to the impeller. Preferably a protective, stationary, static tube 73 is
provided to extend through the hollow confines of the rotating spindle to conduct
10 rock material from the hooper to the impeller while isolating the rock material from
damaging and wearing contact with the interior surface of the rotating spindle, as seen
in FIG 2. Of course, rock and ore is then ejected from the rotating impeller at high
speed, for shattering impact within an encircling annular rock impact chamber
surrounding the impeller member. Crushed rock product then falls from the annular
15 chamber and enters a discharge hopper apparatus for discharge from the crusher as
finished product.

This invention also provides that the impeller-encircling annular chamber, in the
preferred embodiment of the invention, may be supported on an elevator frame
mounted for vertical movement on the main frame of the crusher apparatus, for
20 vertical movement of the annular chamber between a first, operative, impeller-
encircling position for operation of the crusher apparatus, and a second, maintenance
position in which the elevator is moved to move the supported annular chamber
vertically out of impeller-encircling position. This allows repair personnel

unhindered access to the impeller and drive spindle assemblies and to the interior of the annular chamber for facilitated inspection, servicing and replacement of parts, including the entire impeller as a single member, for minimal down-time of the machine for maintenance. This vertically-movable annular rock chamber
5 construction also allows, as has been previously described, for automated operation and control of the elevator drive mechanism to move the chamber slowly upwardly and downwardly within a predetermined range during operation of the crusher apparatus in order to vertically even out the wear against the interior surfaces of the chamber resulting from the impacting of rock and or material ejected from the
10 rotating impeller during operation of the crusher.

There is also disclosed a quick release and attachment mounting connection arrangement, referred to as a gunlock type connection in the particular embodiment illustrated, for releasably securing the impeller onto the bottom end of the drive spindle. This further assists in the facilitation of maintenance operations and reduced
15 downtime of the crusher apparatus.

The suspended impeller construction of the present invention also allows for the provision of a swingable servicing boom member 35, 36 mounted on the main frame and arranged to be operable for engaging, supporting and carrying an impeller member during installation and removal maintenance operations, as explained in
20 connection with FIGS 3 and 6 of the drawings.

From the foregoing it will be readily apparent to those skilled in the art that many changes, other than those already discussed, may be made in the size, shape, type, number and arrangement of parts and structures shown and described hereinbefore

without departing from the spirit of this invention and the scope of the appended claims.

Having thus described our invention and the manner in which it operates, we claim: